

EG - Luxrite

Model Reference	Luminaire Power (tcW)	Lamp Output (lm)	Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Fixture Warranty (Years)	Lamp Warranty (Years)	Power Factor	Life L70/F50 (Khours)
EG001	4.6	355	77.2	2700	80	0.4, 0.75 (/TW), 0.3 (/TK)	220 - 240	50 - 60	IP20	IP20	<6	0	25	5	1	0.50	15
EG002	4.6	370	80.4	3000													
EG003	4.6	390	84.8	4000													

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes.

GDS-415T-REV1 22/03/2022



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

