

ECHO - AEH

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B50 (hours)	Diameter (mm)
AEH001	52.0	4775	91.8	4000	>80	22.3	6.5	220-240	50-60	IP20	IP20	25	5	>0.9	50,000	600
AEH002	158.2	15700	99.2	4000	>80	21.7	22.0	220-240	50-60	IP20	IP20	25	5	>0.9	50,000	1200

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-350T-REV1 27/01/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

