LINGO-LTS

DATASHEET








Key Features

- High performance, high output, LED track spotlight
- Philips Premium White Ra90 LED module
- Highly efficient passive heatsink
- Low glare 40° multi-faceted reflector as standard
- Compatible with Global Trac, Stucchi and Eutrac systems
- DALI dimming option
- Life up to >50,000 hours (L70 / B10)

Technical Drawing















Declaration of Conformity available

Ordering Information

Model Ref.	Colour	Power	Luminaire Output	
		(tcW)	(llm)	
LTS001	930	11.5	1150	
LTS002	940	11.5	1250	
LTS003	930	19.5	1800	
LTS004	940	19.5	1925	
LTS005	930	27.0	2425	
LTS006	940	27.0	2600	
LTS007	930	43.5	3450	
LTS008	940	43.5	3725	

Options

Please select from the options below.

White body, white heatsink	/WH
Black body, grey heatsink	/BKGY
Black body, black heatsink	/BK
DALI dimming	/DALI
24° narrow beam reflector	/NB
60° wide beam reflector	/WB
Barn doors	/BD
Snoot	/SN

LINGO - LTS OPTIONS AND ACCESSORIES





Options



/DALIDALI dimming



/NB 24° narrow beam reflector



/WB 60° wide beam reflector



/BD Barn doors



/SN Snoot



/WH White - RAL9016



/BKGY Black - RAL9005 / Grey - 9007



/BK Black - RAL9005



/HC Honeycomb louvre



9000/BP-D-WSurface mounting pattress - White



9000/BP-D-BSurface mounting pattress - Black



Product variationsOther colours and specifications available on request



Tridonic modules See Lingo LTT datasheet



Xicato modules Contact Sales



TrackSee Stucchi ONETRACK datasheet









