BERLIN - AGI DATASHEET








Key Features

- Mini high output, low glare LED scoop
- Fully adjustable die cast body
- Philips LED and driver system
- Premium White Ra90 LED module as standard
- 24° reflector as standard with 12° and 40° options
- No visible flicker (IEEE 1789 2015)
- ETL and Part L compliant variants
- Lumen maintenance L70/B10 @ >50,000 hours
- 5 year warranty

Technical Drawing

















Declaration of Conformity available

Ordering Information

Model Ref.	Colour	Power	Luminaire Output	
		(tcW)	(llm)	
AGI001	930	10	975	
AGI002	940	10	1050	
AGI003	930	16	1650	
AGI004	940	16	1775	
AGI005	930	27	2450	
AGI006	940	27	2625	

Options

Please select from the options below.

12° Multi- faceted reflector	/NB
40° Multi- faceted reflector	/WB
Touch dimming / DALI	/T+DALI
Casambi wireless network (inc dim)	/BTC
Emergency (remote indicator)	/EM
DALI Emergency (remote indicator)	/EMD

BERLIN - AGI OPTIONS AND ACCESSORIES





Options



/NB 12° narrow beam reflector



/WB 40° wide beam reflector



T+DALITouch dimming / DALI



/BTC Casambi wireless network (inc dim)



/EM EM conversion



/EMDDALI and self test EM conversion









