

## Boston - AEI

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	LOR (%)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/F10 (hours)
AEI001	10.0	1072	107.2	84	3000	80	1.4	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
AEI002	8.9	1000	112.4	84	4000	80	1.4	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
AEI003	18.1	1994	110.2	84	3000	80	1.4	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
AEI004	17.7	2009	113.5	84	4000	80	1.4	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
AEI005	30.6	2985	97.5	84	3000	80	1.4	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
AEI006	29.4	3019	102.7	84	4000	80	1.4	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000

**Please note:** Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-356T 17/072023



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 (0)1924 482777  
www.gamma-uk.com

