

Dallas - AFB

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	LOR (%)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/F10 (hours)
AFB001	14.7	1588	108.0	76	3000	80	2.5	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	96,000
AFB002	14.7	1672	113.7	76	4000	80	2.5	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	96,000
AFB003	22.8	2396	105.1	76	3000	80	2.5	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	96,000
AFB004	20.9	2323	111.1	76	4000	80	2.5	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	96,000
AFB005	28.8	2957	102.7	76	3000	80	2.5	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	96,000
AFB006	25.1	2918	116.3	76	4000	80	2.5	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	96,000

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE. MDS-203T

GDS-351T 19/07/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

