

Milan - ABF

Model Reference	Module Power (W)	Module Output (lm)	Module Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	LOR (%)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/F10 (hours)
ABF002	6.0	470	78.3	6.0	369	61.5	79	2200 - 2700	80	0.75	220-240	50-60	IP20	6	-20	35	3	0.70	25,000
ABF003	8.0	806	100.8	8.0	621	77.6	77	2700	80	0.75	220-240	50-60	IP20	6	-20	35	1	0.75	15,000

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-243T 17/07/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

