

## Montana - AJI

Model Reference	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/F10 (hours)
AJI101	13.5	1376	102.2	3000	80	21.0	2.0	220-240	50-60	IP20	IP20	4	-25	35	3	0.88	44,000
AJI102	13.5	1466	108.9	4000		21.2											
AJI103	22.7	2141	94.2	3000		22.5											
AJI104	22.7	2281	100.4	4000		22.7											
AJI1501	15.7	1927	122.5	3000		22.1						3			5	0.92	>72,000
AJI1502	15.7	2017	128.2	4000		22.3											
AJI4001	20.2	2624	129.6	3000		23.3											
AJI4002	20.2	2746	135.6	4000		23.4											

**Please note:** Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-204T-REV2 18/07/2023



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 (0)1924 482777  
www.gamma-uk.com

