

TOPAZ - ACE

Model Reference	Luminaire Power (tcW)	Engine Output (lm)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B0/F0 (hours)
ACE001	10.3	562	474	46.1	2700	90	0.5	220-240	50-60	IP20	IP20	≤1 X 2	-25	35	5	>0.9	50,000
ACE002	10.3	598	504	49.1	3000												
ACE003	10.3	639	539	52.5	4000												
ACE004	14.2	737	622	43.7	2700												
ACE005	14.2	784	662	46.5	3000												
ACE006	14.2	839	708	49.7	4000												
ACE007	19.1	995	839	43.8	2700												
ACE008	19.1	1058	893	46.6	3000												
ACE009	19.1	1132	955	49.9	4000												

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-368T 29/01/2019



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

