

LINGO - LTT

Model Reference	Module Power (W)	Module Output (lm)	Module Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	LOR (%)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/F10 (hours)
LTT001	25.0	3516	140.6	29.4	2953	100.4	84	3000	>80	1.3	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
LTT002	25.0	3666	146.6	29.4	3079	104.7	84	4000	>80	1.3	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
LTT003	31.8	4712	148.2	37.0	3958	107.0	84	3000	>80	1.3	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
LTT004	29.9	4672	156.3	34.8	3924	112.8	84	4000	>80	1.3	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
LTT005	39.9	5436	136.2	44.8	4566	101.9	84	3000	>80	1.3	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000
LTT006	37.8	5448	144.1	42.7	4576	107.2	84	4000	>80	1.3	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60,000

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-356T 28/03/2019



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

