

LINGO - LTX

Model Reference	Module Power (W)	Module Output (lm)	Module Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (llm)	Luminaire Efficacy (llm/tcW)	LOR (%)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B0 (hours)	
LTX001	25.7	3045	118.5	29.5	2558	86.7	84	3000	>80	1.3	220-240	50-60	IP20	IP20	≤1X2	-25	35	5	>0.9	50,000	
LTX002	25.7	3045	118.5	29.5	2558	86.7		4000													
LTX003	34.2	4025	117.7	39.1	3381	86.5		3000													
LTX004	34.2	4025	117.7	39.1	3381	86.5		4000													
LTX005	41.8	4960	118.7	47.0	4166	88.6		3000													
LTX006	41.8	4960	118.7	47.0	4166	88.6		4000													
LTX007	30.5	3035	99.5	34.5	2549	73.9		3000													>95
LTX008	30.5	3035	99.5	34.5	2549	73.9		4000													

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-150T 28/03/2019



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

