

RAPTOR - AFH

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	LOR (%)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B10 (hours)
AFH001	57.0	8016	140.6	4000	80	16.4/23.1	4.5Kg	220-240	50-60	IP30	IP20	3	-25	35	5	0.96	>70,000
AFH002	87.8	11837	134.7			17.8/24.5										0.96	63,000

Beam Angles	Angle	LOR
Std	84° + 35° Oval	89%
MB	34°	90%
WB	92°	88%

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-357T-REV1 22/07/2019



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

