

DURO - ADH

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life (hours) L70/B10
ADH101	78.5	7800	99.4	3000	80	22.9	2	220 - 240	50 - 60	IP20	IP20	<3	-25	35	5	>0.9	>60,000
ADH102	78.5	8133	103.7	4000	80	22.9											
ADH103	105.4	10208	96.8	3000	80	23.8											
ADH104	105.4	10523	99.8	4000	80	23.9											

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-360T 24/02/2020



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

