

SYSION - AJC

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B10 (hours)
AJC1130	9.6	1009	105.2	3000	80	15.4	1.8	220 - 240	50 - 60	IP20	IP20	3	-25	35	5	>0.9	>60
/MF50		1079	112			14.7											
/SP40		998	104			14.3											
AJC1140	9.7	1090	112	4000	80	15.7											
/MF50		1165	120.0			14.9											
/SP40		1078	111.0			14.6											
AJC2030	17.4	1743	100.0	3000	80	17.6											
/MF50		1864	106.9			16.9											
/SP40		1723	98.9			16.5											
AJC2040	17.4	1889	108.4	4000	80	17.9											
/MF50		2019	116			17.2											
/SP40		1867	107			16.8											
AJC3030	30.3	2675	88.2	3000	80	19											
/MF50		2860	94.2			18.3											
/SP40		2645	87.1			17.9											
AJC3040	30.5	2902	95.3	4000	80	19.3											
/MF50		3102	101.8			18.6											
/SP40		2869	94.2			18.2											
AJC5030	46.5	4177	89.9	3000	80	20.5											
/MF50		4465	96			19.8											
/SP40		4129	89			19.4											
AJC5040	46.6	4532	97	4000	80	20.8											
/MF50		4845	104.0			20.1											
/SP40		4480	96.2			19.7											
AJC2000/TUNE	17.7	1740	99.0	2700 - 6500	90	17.4											
/MF50		1860	105.4			16.9											
/SP40		1720	97.4			16.4											

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-205T REV2 20/07/20



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

