

## DURO - AFG

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L90/F10 (hours)
AFG001	10.6	1160	109.1	3000	80	1.7	220-240	50-60	IP65	IP65	3	-25	35	5	>0.9	47,000
AFG002	10.6	1213	114.2	4000												
AFG003	15.5	1603	103.5	3000												
AFG004	15.5	1677	108.3	4000												
AFG101	13.5	1249	92.7	3000												
AFG102	13.5	1331	98.8	4000												
											5			3		30,000

**Please note:** Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-361T-REV2 14/09/2020



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 (0)1924 482777  
www.gamma-uk.com



FS 593079

