

## TITAN - IC

Model Reference	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B10 (hours)
IC1130	9.6	1044	108.9	3000	80	1.8	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	> 60,000
IC1140	9.7	1128	116.0	4000	80											
IC2030	17.4	1804	103.5	3000	80											
IC2040	17.4	1954	112.1	4000	80											
IC3030	30.3	2768	91.2	3000	80											
IC3040	30.5	3002	98.6	4000	80											
IC5030	46.5	4321	93.0	3000	80											
IC5040	46.6	4689	101.0	4000	80											

**Please note:** Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-198T REV2 18/08/2020



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 (0)1924 482777  
www.gamma-uk.com



FS 593079

