

To accompany Luxrite CA Datasheet GDS-408

Luxrite - CA

Model Reference	Luminaire Power (tcW)	Engine Output (lm)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/F50 (hours)
CA001	7.8	750	746	95.7	3000	80	18.4	0.3	220 - 240	50 - 60	IP54	IP20	3	-25°C	+35°C	5	0.87	>50,000
CA002	7.8	769	764	98.1	4000	80	18.5											

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes.

GDS-408T 11/07/2019



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

