

QUINTO - AFE

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/F50 (hours)
AFE001/LO	6.7	525	77.8	3000	90	12.1	0.4	220-240	50-60	IP44	IP20	3	-25	35	5	0.9	>60,000
AFE002/LO				4000		14.5											
AFE001	3000																
AFE002	4000																
AFE003/LO	13.5	1049		3000		12.1	0.7										
AFE004/LO				4000													
AFE003	22.9	2099	3000	14.5													
AFE004			4000														

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-365T 11/04/2019



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

