

# TITAN - ABE

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/F10 (hours)
ABE001	5.8	479	82.5	3000	80	1.4	220-240	50-60	IP54	IP20	3	-25	35	5	0.63	>72,000
ABE002	5.8	502	86.5	4000											0.89	
ABE003	10.2	1076	105.1	3000											0.91	
ABE004	10.2	1126	110.0	4000												
ABE005	15.0	1485	99.2	3000												
ABE006	15.0	1554	103.8	4000												

**Please note:** Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE. MDS-159T-REV3 12/10/2018

GDS-242T-REV1 20/01/2021



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 (0)1924 482777  
www.gamma-uk.com



FS 593079

