

JINGO - AEJ

Model Reference	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/F10 (Khours)
AEJ001	10.1	1109	109.4	3000K	80	0.8	220-240	50/60	IP20	IP20	3	-25°	30	5	>0.9	>55
AEJ001/9	10.1	916	90.4	3000K	90								30			
AEJ003	10.1	1171	115.6	4000K	80								30			
AEJ003/9	10.1	979	96.7	4000K	90								30			
AEJ005	20.6	1978	96.1	3000K	80								25			
AEJ005/9	20.6	1630	79.2	3000K	90								25			
AEJ007	20.6	2086	101.4	4000K	80								25			
AEJ007/9	20.6	1744	84.8	4000K	90								25			

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-341T REV1 20/05/21



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

