

FAME - ABA

ALL DATA IS PER HEAD																			
Model Reference (Single)	Model Reference (Twin)	Model Reference (Triple)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Power Factor (/TOP)	Life (Khours)
ABA001	ABA201	ABA301	8.0	1020	126.9	3000	80	1.2 / 1.7 / 2.2	220 - 240	50 - 60	IP20	IP20	3	-25	35	5	0.50	0.81	>55
/MF25	/MF25	/MF25		1035	128.8														
/MF60	/MF60	/MF60		901	112.1														
/SP40	/SP40	/SP40		1020	126.9														
/SA50	/SA50	/SA50		889	110.6														
ABA002	ABA202	ABA302		1055	131.3														
/MF25	/MF25	/MF25		1070	133.1	4000													
/MF60	/MF60	/MF60		932	116.0														
/SP40	/SP40	/SP40		1055	131.3														
/SA50	/SA50	/SA50		919	114.3														
ABA003	ABA203	ABA303		1725	124.9												3000		
/MF25	/MF25	/MF25		1750	126.7														
/MF60	/MF60	/MF60	1524	110.3															
/SP40	/SP40	/SP40	1725	124.9															
/SA50	/SA50	/SA50	1503	108.8															
ABA004	ABA204	ABA304	1787	129.4	4000														
/MF25	/MF25	/MF25	1814	131.3															
/MF60	/MF60	/MF60	1579	114.3															
/SP40	/SP40	/SP40	1787	129.4															
/SA50	/SA50	/SA50	1558	112.8															
ABA005	ABA205	ABA305	2363	123.1		3000													
/MF25	/MF25	/MF25	2398	124.9															
/MF60	/MF60	/MF60	2088	108.7															
/SP40	/SP40	/SP40	2370	123.4															
/SA50	/SA50	/SA50	2059	107.2															
ABA006	ABA206	ABA306	2442	127.2	4000														
/MF25	/MF25	/MF25	2479	129.1															
/MF60	/MF60	/MF60	2158	112.4															
/SP40	/SP40	/SP40	2449	127.6															
/SA50	/SA50	/SA50	2129	110.9															
ABA007	ABA207	ABA307	3146	113.1		3000													
/MF25	/MF25	/MF25	3193	114.8															
/MF60	/MF60	/MF60	2779	99.9															
/SP40	/SP40	/SP40	3155	113.4															
/SA50	/SA50	/SA50	2742	98.6															
ABA008	ABA208	ABA308	3252	116.9	4000														
/MF25	/MF25	/MF25	3300	118.7															
/MF60	/MF60	/MF60	2873	103.3															
/SP40	/SP40	/SP40	3261	117.3															
/SA50	/SA50	/SA50	2834	101.9															

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-227T-REV2 12/10/20



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

