





Key Features

- Maintained operation
- 15 x high intensity LEDs for bright, uniform illumination of legend panel
- Screen printed opal polycarbonate legend panel conforms to requirements of EU signs directive
- ISO signage also available
- Supplied with arrow down legend (EU)
- DALI / self-test version available



Technical Drawing



CE R

Declaration of Conformity available

X

J L 7 N

DC

Ordering Information

Rated Duration	Recharge Time	Typical Life	Model Ref.
(hours)	(hours)	(hours)	
3	24	50,000	LSX005

Options

DALI / self-test	/EMD
Arrow right legend panel (EU)	LXSR
Arrow left legend panel (EU)	LXSL
Arrow up legend panel (EU)	LXSWBUP
Arrow right legend panel (ISO)	LXSR/IS0
Arrow left legend panel (ISO)	LXSL/ISO
Arrow up legend panel (ISO)	LXSWBUP/IS0
Arrow down legend panel (ISO)	LXSWBAD/ISO

Thornhill Road Business Park Tenter Fields, Dewsbury West Yorkshire WF12 9QT +44 (0)1924 482777 www.gamma-uk.com







Please note: specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE. GDS-148-REV4 18/10/2021