

EG - Bussy

Model Reference	Luminaire Power (tcW)	Lamp Output (lm)	Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Fixture Warranty (Years)	Lamp Warranty (Years)	Power Factor	Life L70/F50 (Khours)												
EG004	4.9	355	72.4	2700	90	0.4, 0.75 (/TW), 0.3 (/TK)	220 - 240	50 - 60	IP20	IP20	<6	0	25	5	1	0.80	25												
EG005	4.9	365	74.5	3000																									
EG006	4.9	380	77.6	4000																									
EG007	5.5	355	64.5	2700																									
EG008	5.5	375	68.2	3000																									
EG009	5.5	400	72.7	4000																									
																													40

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes.

GDS-441 22/03/2022



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

