

TOPAZ ACC

Model Reference	Luminaire Power (td/W)	Engine Output (lm)	Luminaire Output (lm)	Luminaire Efficacy (lm/td/W)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Life L90/F10 (hours)
ACC001	8.2	596	464	56.9	2700	90	0.3Kg	220 - 240	50 - 60	IP44	IP20	3	-25°C	+35°C	5	>55,000
ACC002	6.7	652	508	96.1	3000	80								+35°C	5	>55,000
ACC003	6.7	689	537	101.5	4000	80								+35°C	5	>55,000
ACC004	10.1	828	645	64.1	2700	90								+25°C	5	>55,000
ACC005	8.2	844	658	80.4	3000	80								+25°C	5	>55,000
ACC006	8.2	892	695	84.9	4000	80								+25°C	5	>55,000

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS 288T REV4 02/03/2020



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

