

To accompany Note AGE Datasheet GDS-381-REV3

Note - AGE

Model Reference	Luminaire Power (tcW)	Engine Output (lm)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Life L70/F10 (Khours)	Life L70/F50 (Khours)
AGE001	8.2	524	365	44.8	2700	90	15.1	0.3	220-240	50-60Hz	IP44	IP20	3	-25	35	5	>55	
AGE002	6.7	560	390	58.3	3000	80	15.4										>55	
AGE003	6.7	592	413	61.6	4000	80	15.6										>55	
AGE004	10.0	712	496	49.6	2700	90	16.2										>55	
AGE005	8.2	718	500	61.3	3000	80	16.2										>55	
AGE006	8.2	758	529	64.8	4000	80	16.4										>55	
AGE007/9	15.3	1153	669	43.8	3000	90	13.7											

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-381T-REV4 07/10/2022



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

