

## SYSION - SRE

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B10 (hours)
SRE1130/XYZ	13.9	1178	84.6	3000	80	17	3	220 - 240	50 - 60	IP20	IP20	3	-25	35	5	>0.9	>60
/MF50		1259	90			15.4											
/SP40		1164	84			14.9											
SRE1140/XYZ	13.9	1282	92	4000	80	17.4											
/MF50		1371	98.4			15.7											
/SP40		1268	91.0			15.2											
SRE2030/XYZ	24.1	1891	78.4	3000	80	18.8											
/MF50		2022	83.8			17.1											
/SP40		1870	77.5			16.5											
SRE2040/XYZ	24.1	2063	85.5	4000	80	19.1											
/MF50		2205	91			17.4											
/SP40		2039	85			16.9											
SRE3030/XYZ	34.7	2537	73.2	3000	80	19.8											
/MF50		2712	78.3			18.1											
/SP40		2508	72.4			17.7											
SRE3040/XYZ	34.8	2769	79.6	4000	80	20.1											
/MF50		2960	85.1			18.4											
/SP40		2737	78.7			18											
SRE5030/XYZ	46.3	3474	75.0	3000	80	20.9											
/MF50		3713	80			19.2											
/SP40		3434	74			18.8											
SRE5040/XYZ	46.4	3792	82	4000	80	21.2											
/MF50		4054	87.4			19.5											
/SP40		3749	80.8			19.1											

**Please note:** Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-168T-REV2 11/10/2022



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 (0)1924 482777  
www.gamma-uk.com



FS 593079

