

To accompany Aspen CF Datasheet GDS-418

## Aspen CF

Model Reference	Luminaire Power (tcW)	Luminaire Output (Lim)	Luminaire Efficacy (Lim/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Life L70/B50 (Khours)
CF001	9	835	93	3000/4000/5500*	80	29.5	0.24	220 - 240	50 - 60	IP54	IP20	6	-25	25	3	50

\*Factory default is 4000K

**Please note:** Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C at 4000K. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-418T 27/04/2023



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 (0)1924 482777  
www.gamma-uk.com



FS 593079

