

To accompany Denver CC Datasheet GDS-410

DENVER - CC

| Model Reference | Luminaire Power (tcW) | Engine Output (lm) | Luminaire Output (lm) | Luminaire Efficacy (lm/tcW) | Light source Efficacy (lm/W) | Colour Temperature (K) | Colour Rendering (Ra) | Nominal Weight (kg) | Mains Voltage (V) | Mains Frequency (Hz) | Ingress Protection (Front) | Ingress Protection (Rear) | MacAdam (SDCM) | Minimum Operating Temperature (°C) | Maximum Operating Temperature (°C) | Warranty (Years) | Life L70/F50 (hours) |
|-----------------|-----------------------|--------------------|-----------------------|-----------------------------|------------------------------|------------------------|-----------------------|---------------------|-------------------|----------------------|----------------------------|---------------------------|----------------|------------------------------------|------------------------------------|------------------|----------------------|
| CC001 | 7.8 | 750 | 746 | 95.7 | 135.0 | 3000 | 80 | 0.3 | 220 - 240 | 50 - 60 | IP54 | IP20 | 3 | -25°C | +35°C | 5 | >50,000 |
| CC002 | 7.8 | 769 | 764 | 98.1 | 139.0 | 4000 | 80 | | | | | | | | | | |

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes.

GDS-410T-REV1 27/04/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com



FS 593079

