

## Viro - AEC

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Life L80/F10 (hours)
AEC001	8.9	809	90.6	3000	80	1.4 1.9 (/EMI & /EMDI)	220-240	50/60	IP20	3	-25	35 25 (/EMI & /EMDI)	5	>72
AEC002	8.9	850	95.2	4000	80									
AEC003	16.1	1522	94.6	3000	80									
AEC004	16.1	1600	99.5	4000	80									
AEC005	23.7	2203	93.0	3000	80									
AEC006	23.7	2316	97.7	4000	80									

**Please note:** Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-344T-REV1 05/05/2023



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 (0)1924 482777  
www.gamma-uk.com

