

Berlin - AGI

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B10 (hours)
AGI001	9.9	960	97.3	3000	90	0.86	220-240	50-60Hz	IP20	IP20	3	-25°	30	5	>0.9	>50,000
AGI002	9.9	1034	104.8	4000	90								30			
AGI003	16.0	1633	102.1	3000	90								30			
AGI004	16.0	1760	110.0	4000	90								30			
AGI005	27.1	2427	89.7	3000	90								25			
AGI006	27.1	2616	96.7	4000	90								25			

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-395T 18/07/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

