



## Key Features

- Professional wall mounted LED uplight
- Philips LED module and driver system
- Opal acrylic diffuser for homogeneous illumination
- Presence and daylight sensor options
- Integral emergency and dimming options
- Aids LG7 compliance

# Technical Drawing









#### Options

Please select from the options below.

Black body	/вк
Presence and daylight sensor	/EA
Touch dimming / DALI	/T+DALI
EM conversion	/EM
Please see accessories sheet	Accessories

#### Ordering Information


Luminaire Output (llm)	Power (tcW)	Colour	Model Ref.
1625	15	830	AFB001
1625	15	840	AFB002
2350	23	830	AFB003
2350	21	840	AFB004
2950	29	830	AFB005
2950	25	840	AFB006

**DALLAS - AFB** OPTIONS AND ACCESSORIES







### Options



**/T+DALI** Touch dimming / DALI



**/EA** Presence and daylight sensor



**/EM** EM conversion



**/BK** Black (RAL 9005)

## Also Available



**Product variations** Other colours and specifications available on request

Thornhill Road Business Park Tenter Fields, Dewsbury West Yorkshire WF12 9QT +44 (0)1924 482777 www.gamma-uk.com



Please note: specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE. GDS-351-REV1 19/07/2023 2 of 2