

To accompany Petra TLW datasheet **GDS-184-REV7**

Petra - TLW

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/F10 (hours)
TLW001	15.3	362	23.6	3000	80	1.4	220-240	50-60	IP20	IP20	3	-25	35	5	0.91	>72,000
TLW002	15.3	379	24.7	4000	80											
TLW003	10.3	264	25.8	3000	80											
TLW004	10.3	276	26.9	4000	80											

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-184T-REV1 19/07/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

