

Reno - AHJ

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B0/F0 (hours)
AHJ001	9.9	965	97.8	3000	90	0.63	220-240	50 - 60	IP20	IP20	3	-25°	30	5	>0.9	>50,000
AHJ002	10.0	1040	104.0	4000	90								30			
AHJ003	16.0	1638	102.4	3000	90								30			
AHJ004	16.0	1765	110.3	4000	90								30			
AHJ005	27.1	2435	90.0	3000	90								25			
AHJ006	27.1	2625	97.0	4000	90								25			

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-396T 17/07/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

