


Key Features

- Incorporating the Philips Fortimo DLM Flex and Xitanium driver
- High efficiency clear PMMA refractor
- 2 m suspension kit as standard, 5 m option available
- Dimming options
- Colour combinations for gear housing available on request
- Lumen maintenance L70/B10 @ up to >60,000 hours
- Emergency options available

Technical Drawing



Ordering Information

Luminaire Output (llm)	Power (tcW)	Colour	Model Ref.
1025	10	830	ID1130
1100	10	840	ID1140
1925	20	830	ID2030
2075	20	840	ID2040
2700	30	830	ID3030
2925	30	840	ID3040
4200	46	830	ID5030
4550	46	840	ID5040

Options

Please select from the options below.

Touch dimming / DALI			/T+DALI
5 m suspension kit			/5M
W = White	B = Black	G = Grey	Part X
W = White	B = Black	G = Grey	Part Y

Please note: specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE. **GDS-197-REV11 18/07/2023** 1 of 2

TAHITI - ID OPTIONS AND ACCESSORIES

PHILIPS TECHNOLOGY INSIDE



Options




/T+DALI Touch dimming / DALI



/5M 5 m suspension kit



Emergency conversions Contact Sales



Any RAL colour Contact Sales

Code examples



/BB Black, Black



/GG Grey, Grey



/WB White, Black

Thornhill Road Business Park Tenter Fields, Dewsbury West Yorkshire WF12 9QT +44 (0)1924 482777 www.gamma-uk.com



Please note: specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE. **GDS-197-REV11 18/07/2023** 2 of 2