

Tahiti - ID

Model Reference	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B10 (hours)
ID1130	9.9	1014	102.9	3000	80	8.8	2.8	220-240	50-60	IP20	IP20	3	-25	35	5	>0.9	>60
ID1140	9.9	1095	111.1	4000	80	9.5								35			>60
ID2030	19.5	1925	98.5	3000	80	11.5								35			>60
ID2040	19.5	2085	106.7	4000	80	11.7								35			>60
ID3030	30.2	2694	89.1	3000	80	11.8								35			>60
ID3040	30.3	2922	96.3	4000	80	12.1								35			>60
ID5030	46.4	4188	90.3	3000	80	13.3								35			58
ID5040	46.4	4543	98.0	4000	80	13.6								35			58

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-197T REV2 18/07/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

