PROFLUX - AFD

DATASHEET








Key Features

- Extruded direct/indirect linear profile luminaire
- Typical percentage output ratio 75 : 25
- Finished in RAL 9006 grey as standard
- Available in 3 standard lengths
- Delivering approx. 3000 llm/m as standard
- Coloured matched, injection moulded end caps
- TPa opal lens for feature, general and visual areas
- Low glare prismatic lens available to aid LG7 compliance
- Tridonic low energy LED and driver system
- Lumen maintenance L80/F10 @ >72,000 hours
- Efficacy up to 130 llm/tcW
- Manufactured in the U.K.
- 2 m suspension kit

Technical Drawing















Declaration of Conformity available

Ordering Information

Length	Colour	Luminaire Output (llm) Std	Model Ref.	Luminaire Output (llm) /L0	Luminaire Output (llm) /HO
850 mm	830	2300	AFD001	1550	3650
850 mm	840	2400	AFD002	1625	3825
1.2 m	830	3450	AFD003	2325	5475
1.2 m	840	3600	AFD004	2450	5725
1.5 m	830	4450	AFD005	3000	7050
1.5 m	840	4650	AFD006	3150	7375

For longer lengths, see Proflux AGD

Options

Please select from the options below.

White body	/WH
Black body	/BK
Lower output	/LO
Higher output	/H0
Low glare prismatic lens for LG7 compliance	/LG
SwitchDIM, DALI or DSI	/ECO
EM conversion (not AFD001 / AFD002)	/EMI
Butt joints	/BU

PROFLUX - AFD

OPTIONS AND ACCESSORIES






Options




/WH White body




/BKBlack body



/L0Lower output



/HO Higher output



/ECO SwitchDIM, DALI or DSI



/EMI EM conversion



/LGLow glare prismatic lens

Also Available




BU.164/180 180° Butt joint bracket



BU.164/90 90° Butt joint bracket



Product variationsOther colours and specifications available on request



Product variationsCustom body colours



Product variationsCustom colours



PT001Diffuser removal tool

Thornhill Road Business Park Tenter Fields, Dewsbury West Yorkshire WF12 9QT +44 [0]1924 482777

www.gamma-uk.com









