

Aspen - CI

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	UGR	BLF (EM ONLY)	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Life L70/B50 (Khours)	ENERGY CLASS (4000K @ 500mA)
CI001	3000	80	172	13.5	1625	120	26.9	0.9	220 - 240	50 - 60	IP54	IP20	-20.0	25.0	5	50	C	
	4000		172	13.0	1625	125	26.6											16%
	5700		154	13.5	1475	109	26.1											18%
CI002	3000		160	19.0	2250	118	27.9											11%
	4000		163	18.5	2275	123	27.8											11%
	5700		144	19.0	2025	107	27.2											12%
CI003	3000		152	23.0	2625	114	28.4											10%
	4000		157	22.0	2700	123	28.3											10%
	5700		137	23.0	2350	102	27.7											11%
CI004	3000		142	31.5	3325	106	29.2											7%
	4000		149	30.0	3500	117	29.2											7%
	5700		130	31.5	3025	96	28.6											8%

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-444T 09/06/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

