

RAPTOR - AFH

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Light Source Power (W)	Light Source Output (lm)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	UGR	BLF (EM ONLY)	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/B10 (Khours)	Light Source Energy Class
AFH001	4000	80	51	9007	176	57	8025	141	16.4/23.1	8%	4.5Kg	220-240	50-60	IP30	IP20	3	-25	35	5	>0.94	56	C
AFH002			82	13300	163	88	11850	135	17.8/24.5	5%										>0.94	47	C

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-357T-REV2 24/01/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

