

TITAN - ABE

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Light Source Power (W)	Light Source Output (lm)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	UGR	BLF (EM ONLY)	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/B10 (Khours)	Light Source Energy Class
ABE001	3000	80	5.0	1025	205	7.0	700	100	22	0.36	1.4Kg	220-240	50-60Hz	IP54	IP20	3	-25	35	5	0.80	>72	C
ABE002	4000	80	5.0	1075	215	7.0	725	104	22	0.36								35		0.80		C
ABE003	3000	80	8.5	1650	194	10.5	1125	107	23	0.20								35		>0.9		C
ABE004	4000	80	8.5	1725	203	10.5	1175	112	23	0.21								35		>0.9		C
ABE005	3000	80	12.5	2250	180	14.0	1525	109	24	0.15								35		>0.9		C
ABE006	4000	80	12.5	2375	190	14.0	1600	114	25	0.16								35		>0.9		C
ABE007	3000	80	18.0	3100	172	20.5	2100	102	25	0.11								35		>0.9		C
ABE008	4000	80	18.0	3250	181	20.5	2225	109	26	0.11								35		>0.9		C

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-242T-REV2 20/12/2023



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

