

ECHO - AEF

Model Reference	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B50 (hours)	Diameter (mm)
AEF001	47.0	2625	55.9	4000	>80	23.0	6.0	220-240	50-60	IP20	IP20	25	5	>0.9	50,000	600
AEF002	83.0	5025	60.5	4000	>80	22.6	15.6	220-240	50-60	IP20	IP20	25	5	>0.9	50,000	1200

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-352T REV3 22/02/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

