

Aspen CF

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Module Power (W)	Module Output (lm)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	LOR (%)	UGR	BLF (EM ONLY)	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Life L70/B50 (khours)	ENERGY CLASS (4000K @ 500mA)
CF001	3000	80	7	900	121	9	750	82	82%	29.1	25%	0.24	220 - 240	50 - 60	IP54	IP20	6	-25	25	3	50	E
	4000*			1018	137		850	93		29.5												
	5500			941	127		775	86		29.3												

*Factory default is 4000K

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C at 4000K. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-418T-REV1 15/01/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

