

QUINTO - AFF

Model Reference	Luminaire Power (tcW)	Luminaire Output (lm)	Luminaire Efficacy (lm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/F50 (hours)
AFF001/LO	6.7	525	77.8	3000	90	0.7	220-240	50-60	IP20	IP20	3	-25	35	5	0.9	>60,000
AFF002/LO				4000												
AFF001	3000															
AFF002	4000															
AFF003/LO	3000															
AFF004/LO	4000															
AFF003	22.9	2099	91.5	3000	1.2											
AFF004				4000												

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-366T-REV1 12/03/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

