

AGJ NOTE

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Light Source Power (W)	Light Source Output (lm)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Lm)	Luminaire Efficacy (Lm/tcW)	UGR	BLF (EM ONLY)	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/F10 (Hours)	LIGHT SOURCE ENERGY CLASS
AGJ001	2700	90	5.5	800	139	7.5	550	75	11.7	33%	0.25	220 - 240	50 - 60	IP54	IP20	3.0	-25.0	35.0	5	>0.90	>60	E
AGJ002	3000	80	4.5	850	177	6.0	575	95	11.8	40%												D
AGJ003	4000		4.5	900	188	6.0	600	100	12.0	40%												C
AGJ004	2700	90	8.0	1075	134	9.5	725	75	12.6	24%												E
AGJ005	3000	80	6.0	1100	174	7.5	750	100	12.7	30%												D
AGJ006	4000		6.0	1150	180	7.5	775	105	12.9	30%												C

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-460T 10/04/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

