

MONTANA - AJI

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Light Source Power (W)	Light Source Output (lm)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Lim)	Luminaire Efficacy (Lim/tcW)	UGR	BLF (EM ONLY)	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Light Source Energy Class
AJI001	3000	80	8.5	1634	192	11.0	1450	131.8	20.9	21%	2.0	220 - 240	50 - 60	IP20	IP20	3	-25	35	5	>0.90	C
AJI002	4000		8.5	1719	202	11.0	1525	138.6	21.1	21%										>0.90	
AJI003	3000		12.5	2248	180	15.0	2000	133.3	22.1	15%										>0.95	
AJI004	4000		12.5	2365	189	15.0	2100	140.0	22.2	15%										>0.95	
AJI005	3000		17.5	3153	180	20.5	2775	135.4	23.1	11%										>0.95	
AJI006	4000		17.5	3310	189	20.5	2925	142.7	23.3	11%										>0.95	
AJI007	3000		24.5	4233	173	28.0	3750	133.9	24.2	8%										>0.95	
AJI008	4000		24.5	4445	181	28.0	3925	140.2	24.4	8%										>0.95	

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-204T-REV3 02/04/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

