

## NOTE - AGB

Model Reference	Luminaire Power (tcW)	Engine Output (lm)	Luminaire Output (llm)	Luminaire Efficacy (llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B50 (hours)
AGB001	9.5	710	618	65.0	2700	90	0.25	220-240	50-60	IP54	IP20	3	-25°	35	5	>0.9	>50,000
AGB002	9.5	760	661	69.6	3000											0.53	
AGB003	9.5	810	705	74.2	4000											0.54	
AGB004	10.6	770	670	63.3	2700											0.53	
AGB005	10.6	840	731	69.1	3000											0.53	
AGB006	10.6	890	774	73.2	4000											0.53	
AGB007	14.3	1140	992	69.6	2700											0.54	
AGB008	14.3	1170	1018	71.4	3000											0.54	
AGB009	14.3	1270	1105	77.5	4000											0.54	

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-398T-REV1 03/04/2024



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 (0)1924 482777  
www.gamma-uk.com

