

Note - AGE

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Light Source Power (W)	Light Source Output (lm)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Lim)	Luminaire Efficacy (Lim/tcW)	UGR	BLF (EM ONLY)	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/F10 (Khours)	LIGHT SOURCE ENERGY CLASS
AGE001	2700	90	5.5	800	139	7.5	375	50	15.1	33%	0.3	220-240	50-60Hz	IP44	IP20	3	-25°	35	5	0.9	>60	E
AGE002	3000	80	4.5	850	177	6.0	400	65	15.3	40%								35	5	>0.85	>60	D
AGE003	4000	80	4.5	900	188	6.0	425	70	15.9	40%								35	5	>0.85	>60	C
AGE004	2700	90	8.0	1075	134	9.5	525	55	16.6	24%								25	5	>0.50	>60	E
AGE005	3000	80	6.0	1100	174	7.5	525	70	16.3	30%								25	5	>0.50	>60	D
AGE006	4000	80	6.0	1150	180	7.5	550	75	16.8	30%								25	5	>0.50	>60	C
AGE007	3000	90	13	1460	113	15	675	45	13.7	15%								25	5	>0.9	>50 (L70/F50)	E

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-381T-REV5 20/05/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

