

INDIA - AFG

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Light Source Power (W)	Light Source Output (lm)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	UGR	BLF (EM ONLY)	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L80/F10 (Khours)	Light Source Energy Class
AFG001	3000	80	9	1595	181	10.0	1200	120	21.6	0.22	1.7	220-240	50-60	IP65	IP65	3	-25	35	5	>0.9	>72	C
AFG002	4000	80	9	1678	191	10.0	1250	125	21.8	0.22										>0.9		C
AFG003	3000	80	13	2154	172	14.0	1600	114	22.6	0.16										>0.9		C
AFG004	4000	80	13	2282	182	14.0	1700	121	22.8	0.16										>0.9		C
AFG005	3000	80	18	2988	164	21.0	2225	106	23.8	0.11										>0.9		C
AFG006	4000	80	18	3144	172	21.0	2350	112	24	0.12										>0.9		C

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-361T-REV3 28/06/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

