

## Oslo AH

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Lumen Maintenance @50K hrs	Light Source Energy Class
AH001	3000	80	19.0	2425	127.6	<19	2.5	220-240	50-60	IP44	IP20	3	-10	25	5	>0.9	L90/B10	C
AH002	4000	80	19.0	2575	135.5	<19												
AH003	3000	80	24.5	3100	126.5	<19												
AH004	4000	80	24.5	3300	134.7	<19												
AH005	3000	80	32.0	3975	124.2	<19												
AH006	4000	80	32.0	4200	131.3	<19												

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-469T 05/11/2024



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 [0]1924 482777  
www.gamma-uk.com

