

Freestyle BJ

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	UGR	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Lumen Maintenance @ 50K hrs	Light Source Energy Class
BJ001	3000	80	29.0	3400	117.2	<19	2.75	220-240	50-60	IP40	IP20	3	-10	25	5	>0.95	L80/B10	C
BJ002	4000	80	27.5	3050	110.9	<19												D
BJ003	3000	80	35.0	4050	115.7	<19												C
BJ004	4000	80	34.0	3625	106.6	<19												D
BJ005	3000	80	39.2	4500	114.8	<19												C
BJ006	4000	80	38.0	3975	104.6	<19												D

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-470T 27/11/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

