

TOPAZ - ACB

Model Reference	Luminaire Power (tcW)	Engine Output (lm)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	UGR	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Life L90/F10 (Khours)	Light Source Energy Class
ACB001	8.0	625	553	69.9	2700	90	<10	0.3	220 - 240	50 - 60	IP44	IP20	3	-25°C	+35°C	5	>55	E
ACB002	6.5	650	582	90.9	3000	80	<10								+35°C	5	>55	D
ACB003	6.5	700	620	96.7	4000	80	<10								+35°C	5	>55	C
ACB004	10.0	850	753	76.3	2700	90	<10								+25°C	5	>55	E
ACB005	7.5	850	769	99.9	3000	80	<10								+25°C	5	>55	D
ACB006	7.5	900	816	106.0	4000	80	<10								+25°C	5	>55	C
ACB007	13.5	1150	1027	76.6	2700	90	<10								+25°C	5	>55	E
ACB008	11.5	1250	1124	98.5	3000	80	<10								+25°C	5	>55	D
ACB009	11.5	1325	1191	104.4	4000	80	<10								+25°C	5	>55	C
ACB201	16.0	1225	1106	69.9	2700	90	<10	0.7	220 - 240	50 - 60	IP44	IP20	3	-25°C	+35°C	5	>55	E
ACB202	13.0	1300	1165	90.9	3000	80	<10								+35°C	5	>55	D
ACB203	13.0	1375	1239	96.7	4000	80	<10								+35°C	5	>55	C
ACB204	20.0	1675	1506	76.3	2700	90	<10								+25°C	5	>55	E
ACB205	15.5	1700	1537	99.9	3000	80	<10								+25°C	5	>55	D
ACB206	15.5	1800	1632	106.0	4000	80	<10								+25°C	5	>55	C
ACB207	27.0	2275	2054	76.6	4000	80	<10								+25°C	5	>55	E
ACB208	23.0	2475	2248	98.5	4000	80	<10								+25°C	5	>55	D
ACB209	23.0	2625	2383	104.4	4000	80	<10								+25°C	5	>55	C
ACB301	24.0	1825	1659	69.9	2700	90	<10	1.1	220 - 240	50 - 60	IP44	IP20	3	-25°C	+35°C	5	>55	E
ACB302	19.0	1925	1747	90.9	3000	80	<10								+35°C	5	>55	D
ACB303	19.0	2050	1859	96.7	4000	80	<10								+35°C	5	>55	C
ACB304	29.5	2500	2260	76.3	2700	90	<10								+25°C	5	>55	E
ACB305	23.0	2550	2306	99.9	3000	80	<10								+25°C	5	>55	D
ACB306	23.0	2700	2449	106.0	4000	80	<10								+25°C	5	>55	C
ACB307	40.0	3400	3081	76.6	4000	80	<10								+25°C	5	>55	E
ACB308	34.0	3725	3373	98.5	4000	80	<10								+25°C	5	>55	D
ACB309	34.0	3950	3574	104.4	4000	80	<10								+25°C	5	>55	C

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-287T-REV5 28/10/2024



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

